MAKE THE RIGHT CHOICE — AND MAKE MORE MONEY.

The X-Cut chain is undoubtedly a great product. But its benefits are only fully taken advantage of when it is mounted on the right saw. On the next page, you can easily find the type of chain that fits your Husqvarna optimally. As you probably know already, the precise matching of chain and saw is crucial for making your output the highest possible.

GUIDE — BARS AND CHAINS

SMALL BAR MOUNTING POINT — **LARGE BAR MOUNTING POINT**

536LiPX / 536LiP4 / 536LiPT5	T425	T435 / 334T	T540XP®	338XPT / 335XPT	327P4 / 327P5X / 525P4S / 525P5S	327PT5S / 525PT5S	317EL / 321EL	136Li	436Li / 536LiXP®	T536LiXP®	137 / 142 / 137 e-series / 142 e-series	240 e-series / 235 e-series / 236 e-series	135 / 140 / 135 e-series, 136 / 141 / 140 e-series	439	339XP®	435 e-series / 435 / 440 e-series	340 / 340 e-series / 345 / 345 e-series / 350 / 351	450 e-series / 445 / 445 e-series	545 / 550XP® / 346XP® / 353	51 / 55 / 357XP® / 359	362XP®	460 / 455 Rancher / 455 e-series Rancher	555 / 560XP®	460 Rancher / 465 Rancher	61 / 268	281XP® / 288XP® / 394XP® / 395XP®	562XP®	365 / 372XP® / 371XP®	576XP® / 575XP® / 570	385XP® / 390XP®	395XP®	3120XP®	HXX	BAR LENGTH	CHAIN PITCH	GAUGE	BAR	CHAIN
						●[1]																											H00	10" / 25 cm	1/4"	.050" / 1.3 mm	**575 84 22–58**	**501 84 40–58**
						●[1]																											H00	12" / 30 cm	1/4"	.050" / 1.3 mm	**575 84 22–64**	**501 84 40–64**
	●																																H37	10" / 25 cm	3/8"	.050" / 1.3 mm	**505 89 16–40**	**576 93 65–40**
									●	●																							H38	10" / 25 cm	3/8"	.043" / 1.1 mm	**501 95 95–40**	**581 80 79–40**
								●	●	●																							H38	12" / 30 cm	3/8"	.043" / 1.1 mm	**501 95 95–45**	**581 80 79–45**
									●	●																							H38	14" / 35 cm	3/8"	.043" / 1.1 mm	**501 95 95–52**	**581 80 79–52**
●						●[2]																											H38	12" / 30 cm	3/8"	.050" / 1.3 mm	**585 82 91–44**	**501 84 70–44**
					●																												H37	10" / 25 cm	3/8"	.050" / 1.3 mm	**501 95 92–40**	**576 93 65–40**
		●	●	●	●		●					●	●	●																			H37	12" / 30 cm	3/8"	.050" / 1.3 mm	**501 95 92–45**	**576 93 65–45**
		●	●	●			●					●	●	●																			H37	14" / 35 cm	3/8"	.050" / 1.3 mm	**501 95 92–52**	**576 93 65–52**
		●	●	●			●					●	●	●																			H37	16" / 40 cm	3/8"	.050" / 1.3 mm	**501 95 92–56**	**576 93 65–56**
											●				●	●	●	●	●														H30	13" / 33 cm	.325"	.050" / 1.3 mm	**585 94 32–56**	**501 84 06–56**
											●				●	●	●	●	●														H30	15" / 38 cm	.325"	.050" / 1.3 mm	**585 94 32–64**	**501 84 06–64**
															●	●	●	●	●														H30	16" / 40 cm	.325"	.050" / 1.3 mm	**585 94 32–66**	**501 84 06–66**
															●	●	●	●	●														H30	18" / 45 cm	.325"	.050" / 1.3 mm	**585 94 32–72**	**501 84 06–72**
																		●	●	●	●	●	●										H25	13" / 33 cm	.325"	.058" / 1.5 mm	**585 94 33–56**	**501 84 04–56**
																		●	●	●	●	●	●										H25	15" / 38 cm	.325"	.058" / 1.5 mm	**585 94 33–64**	**501 84 04–64**
																		●	●	●	●	●	●										H25	16" / 40 cm	.325"	.058" / 1.5 mm	**585 94 33–66**	**501 84 04–66**
																		●	●	●	●	●	●										H25	18" / 45 cm	.325"	.058" / 1.5 mm	**585 94 33–72**	**501 84 04–72**
																		●	●	●	●	●	●										H25	20" / 50 cm	.325"	.058" / 1.5 mm	**585 94 33–80**	**501 84 04–80**
																					●	●	●										H42	15" / 38 cm	3/8"	.058" / 1.5 mm	**585 94 34–56**	**501 84 14–56**
																					●	●	●										H42	16" / 40 cm	3/8"	.058" / 1.5 mm	**508 91 41–60**	**501 84 14–60**
																					●	●	●										H42	18" / 45 cm	3/8"	.058" / 1.5 mm	**585 94 34–68**	**501 84 14–68**
																					●	●	●										H42	20" / 50 cm	3/8"	.058" / 1.5 mm	**585 94 34–72**	**501 84 14–72**
																								●	●	●	●	●	●				H42	15" / 38 cm	3/8"	.058" / 1.5 mm	**585 95 08–56**	**501 84 14–56**
																								●	●	●	●	●	●				H42	16" / 40 cm	3/8"	.058" / 1.5 mm	**508 91 31–60**	**501 84 14–60**
																								●	●	●	●	●	●	●	●		H42	18" / 45 cm	3/8"	.058" / 1.5 mm	**585 95 08–68**	**501 84 14–68**
																								●	●	●	●	●	●	●	●		H42	20" / 50 cm	3/8"	.058" / 1.5 mm	**585 95 08–72**	**501 84 14–72**

LAMINATED BAR WITH NOSE WHEEL, TECHLITE™

		●	●																														H37	12" / 30 cm	3/8"	.050" / 1.3 mm	**576 83 07–45**	**576 93 65–45**
		●								●																							H37	14" / 35 cm	3/8"	.050" / 1.3 mm	**576 83 07–52**	**576 93 65–52**
		●								●																							H37	16" / 40 cm	3/8"	.050" / 1.3 mm	**576 83 07–56**	**576 93 65–56**
							●	●																									H38	14" / 35 cm	3/8"	.043" / 1.1 mm	**578 10 68–52**	**581 80 79–52**

SOLID BAR WITH REPLACEABLE NOSE WHEEL

																					●	●	●	●											H42	18" / 45 cm	3/8"	.058" / 1.5 mm	**501 95 77–68**	**501 84 14–68**
																					●	●	●	●											H42	20" / 50 cm	3/8"	.058" / 1.5 mm	**501 95 77–72**	**501 84 14–72**
																									●	●	●	●	●	●	●	●		H42	18" / 45 cm	3/8"	.058" / 1.5 mm	**501 95 69–68**	**501 84 14–68**
																									●	●	●	●	●	●	●	●		H42	20" / 50 cm	3/8"	.058" / 1.5 mm	**501 95 69–72**	**501 84 14–72**
																									●		●	●	●	●	●	●		H42	24" / 60 cm	3/8"	.058" / 1.5 mm	**501 95 69–84**	**501 84 14–84**
																											●	●	●	●	●	●		H42	28" / 72 cm	3/8"	.058" / 1.5 mm	**501 95 69–92**	**501 84 14–92**

SOLID BAR*

	●																																H00	10" / 25 cm	1/4"	.050" / 1.3 mm	**505 89 15–60**	**501 84 40–60**
								●	●																								H00	10" / 25 cm	1/4"	.050" / 1.3 mm	**587 39 44–60**	**501 84 40–60**
								●	●																								H00	12" / 30 cm	1/4"	.050" / 1.3 mm	**587 39 44–68**	**501 84 40–68**
								●																									H00	12" / 30 cm	1/4"	.050" / 1.3 mm	**579 55 90–68**	**501 84 40–68**
																									●	●	●	●	●	●	●	●		H42	18" / 45 cm	3/8"	.058" / 1.5 mm	**501 95 80–68**	**501 84 14–68**
																									●	●	●	●	●	●	●	●		H42	20" / 50 cm	3/8"	.058" / 1.5 mm	**501 95 80–72**	**501 84 14–72**
																											●	●	●	●	●	●		H42	24" / 60 cm	3/8"	.058" / 1.5 mm	**501 95 80–84**	**501 84 14–84**
																											●	●	●	●	●	●		H42	28" / 72 cm	3/8"	.058" / 1.5 mm	**501 95 80–92**	**501 84 14–92**
																															●	●	H64	24" / 60 cm	.404"	.063" / 1.6 mm	**507 47 60–46**	**501 84 31–76**
																															●	●	H64	28" / 72 cm	.404"	.063" / 1.6 mm	**501 58 96–01**	**501 84 31–84**
																															●	●	H64	30" / 75 cm	.404"	.063" / 1.6 mm	**501 95 81–92**	**501 84 31–92**
																															●	●	H64	36" / 90 cm	.404"	.063" / 1.6 mm	**501 95 81–04**	**501 84 31–04**
																																●	H64	42" / 105 cm	.404"	.063" / 1.6 mm	**501 92 18–24**	**501 84 31–24**

Always check your operator's manual for the cutting equipment that fits your chainsaw.
[1] All except North America. [2] North America * Solid bar with .404" chain pitch on 390 XP® is optional on certain markets.